



# VM750D Body Worn Camera

## Safe, Smart, Transparent

- 160° Diagonal Field of View
- 2.8-inch Screen
- Image Stabilization
- NFC-enabled ID Switchover
- Fast Positioning
- AI-driven Facial Recognition
- Intelligent Scene Detection



VM750D



## Overview

Hytera VM750D Body Worn Camera (BWC) is designed to capture, store, and upload evidence such as pictures, videos, and audio in the field. It plays a leading role in building trust with the public, in promoting officer accountability, and in enhancing transparency between the police and its citizens.

With a 160° diagonal field of view (DFOV), the BWC expands your view in a significant way. So, you can capture more details with this incredible camera. The BWC can also stream the real-time video in the field over 3G, 4G, or WLAN network to the control centre for better situational awareness. The evidence management solution allows you to securely collect, manage, and share all the data from the BWC.

## Highlights



### 160° Diagonal Field of View

The super wide-angle camera allows you to capture more objects in a broader scope. Even at one meter away, the BWC can capture hand movements from targets at close quarters.



### PoC Radio

The BWC serves as a PoC Radio. Over 3G, 4G, or WLAN networks, the device allows you to make a voice call simply by pressing the push-to-talk (PTT) key. Thanks to the advanced noise cancellation technology, the BWC picks up your voice while removing the ambient noise.



### Fast Positioning

The BWC provides fast positioning services by using GPS, GLONASS, BDS, together with AGPS in the public network. Thanks to the advanced position algorithm, the BWC delivers precise location data.



### AES-256 Encryption

VM750D adopts the AES-256 advanced encryption technology to protect all the captured evidence (including images, audio, and videos) in local storage.



### Intelligent Scene Detection

The BWC incorporates the multi-functional sensor that will automatically send an alarm to the control centre when detecting Man-down, occlusion, stay-long, or dismantling.



### Remote Speaker Microphone (RSM)

The VM750D can work with radio as a remote speaker microphone (RSM). After connecting the BWC to a radio through the BT or data cable, you can transmit the voice by pressing the PTT key.



### NFC-enabled ID Switchover

The NFC allows ID switchover just by simply holding the NFC card to the BWC. This simplifies the process of ID switchover, enhances the BWC availability, and reduces unnecessary expenses.



### 2.8-inch Screen

With a 2.8 inch touch screen, users are able to easily operate the device and have visual feedback.



## Accessories



Power Adapter  
MicroUSB



Belt Clip  
Carry Accessory



Shoulder Strap  
Carry Accessory



Magnetic Belt Clip  
Carry Accessory



Wireless Ring PPT  
PTT  
Volume Control



Wired Earpiece



BT Earpiece  
PPT  
Volume control  
Microphone adjustment



13-Pin Connector Cable  
Clip for fixing the RSM



Dock Charger  
One dock for BWC and  
batteries  
With MicroUSB port to  
acquire data



Multi-Unit Charger  
Six docks for BWC and  
batteries  
With MicroUSB port to  
acquire data



## Specifications

Parameter	VM750D		
Dimensions (H x W x D)	116 x 61 x 26 mm		
Weight	210 g (with battery)		
Screen	2.8-inch		
Storage Capacity	32 / 64 / 128 GB		
Battery Capacity	3500 mAh		
Night Vision	Support Infrared night vision		
Field of View	160°diagonal 127°horizontal 67°vertical		
Image Stabilization	Optional		
Focus range	0.5 m to infinity		
Video Resolution	1080p@30fps, 720p@30fps, 480p@30fps		
Video File Format	MP4		
Photo Resolution	40MP,16MP,8MP,5MP		
Photo File Format	JPG		
Audio File Format	AAC		
File Encryption	Support AES-256bit		
WLAN	802.11 b/g/n/ac		
BT	BT 4.2 Support BLE		
Positioning	GPS, BeiDou, GLONASS, AGPS		
Interface	MicroUSB		
RSM Mode	Connect to the radio through the 13-Pin Connector		
Water and Dust Proof	IP68		
Drop-proof Height	2 meters		
Operating Temperature	-30°C to +60°C		
Operating Humidity Range	10% to 95% (non-condensing)		
Cellular networks	<table border="0"> <tr> <td style="vertical-align: top;"> <b>Asia, Europe and Africa Edition:</b>                      GSM: 850/900/1800/1900                      TD-SCDMA: B34/B39                      CDMA: BC0                      WCDMA: B1/B3/B5/B8                      TDD-LTE: B34/B38/B39/B40 /B41                      FDD-LTE: B1/B3/B5/B7/B8/B20/B26/B28                 </td> <td style="vertical-align: top;"> <b>American Edition:</b>                      GSM: 850/1900                      WCDMA: B2/B4/B5                      TDD-LTE: B38/B40/B41                      FDD-LTE: B2/B4/B5/B7/B12/B13                      /B17/B26 /B28                 </td> </tr> </table>	<b>Asia, Europe and Africa Edition:</b> GSM: 850/900/1800/1900 TD-SCDMA: B34/B39 CDMA: BC0 WCDMA: B1/B3/B5/B8 TDD-LTE: B34/B38/B39/B40 /B41 FDD-LTE: B1/B3/B5/B7/B8/B20/B26/B28	<b>American Edition:</b> GSM: 850/1900 WCDMA: B2/B4/B5 TDD-LTE: B38/B40/B41 FDD-LTE: B2/B4/B5/B7/B12/B13 /B17/B26 /B28
<b>Asia, Europe and Africa Edition:</b> GSM: 850/900/1800/1900 TD-SCDMA: B34/B39 CDMA: BC0 WCDMA: B1/B3/B5/B8 TDD-LTE: B34/B38/B39/B40 /B41 FDD-LTE: B1/B3/B5/B7/B8/B20/B26/B28	<b>American Edition:</b> GSM: 850/1900 WCDMA: B2/B4/B5 TDD-LTE: B38/B40/B41 FDD-LTE: B2/B4/B5/B7/B12/B13 /B17/B26 /B28		



### Hytera Communications Europe

939 Yeovil Road, Slough, Berkshire, SL1 4NH

[info@hytera-europe.com](mailto:info@hytera-europe.com) | [www.hytera-europe.com](http://www.hytera-europe.com)



[www.facebook.com/HyteraEurope](https://www.facebook.com/HyteraEurope)



[www.linkedin.com/company/hytera-communications-uk](https://www.linkedin.com/company/hytera-communications-uk)



[www.instagram.com/Hytera.Europe](https://www.instagram.com/Hytera.Europe)



Subscribe on YouTube

Hytera reserves the right to modify the product design and the specifications. In case of a printing error, Hytera does not accept any liability. All specifications are subject to change without notice.